

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
23 June 2005 (23.06.2005)


PCT

(10) International Publication Number  
**WO 2005/057098 A1**

- (51) International Patent Classification<sup>7</sup>: **F25B 39/04**,  
B60H 1/32
- (21) International Application Number:  
PCT/JP2004/018770
- (22) International Filing Date: 9 December 2004 (09.12.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
2003-410665 9 December 2003 (09.12.2003) JP  
60/529,572 16 December 2003 (16.12.2003) US
- (71) Applicant (for all designated States except US): **SHOWA DENKO K.K.** [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo, 1058518 (JP).
- (72) Inventor; and  
(75) Inventor/Applicant (for US only): **OHASHI, Hideo** [JP/JP]; c/o Showa Denko K.K., Oyama Regional Office, 480, Inuzuka 1-chome, Oyama-shi, Tochigi, 3238678 (JP).
- (74) Agents: **HIBI, Norihiko** et al.; c/o Kishimoto & Co., 3rd Floor, Inaba Building, 13-18, Nishishinsaibashi 1-chome, Chuo-ku, Osaka-shi, Osaka, 5420086 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: EVAPORATOR



(57) Abstract: A second fin 27 is disposed outside a refrigerant passing body 2 positioned at one side end of a heat exchange core 4 where a refrigerant inlet 14 and a refrigerant outlet 15 are provided. A side plate 26 is disposed externally of the second fin 27. The second fin 27 and the side plate 26 have respective upper ends so positioned as to permit an upper portion outer surface of the refrigerant passing body 2 to be exposed. A refrigerant inflow member 16 and a refrigerant outflow member 17 are arranged on the refrigerant passing body 2 at an external portion thereof above the second fin 27 and the side plate 26, and the inflow member 16 is connected to the inlet 14, and the outflow member 17 is connected to the outlet 15. The inflow member 16 and the outflow member 17 have respective outer side faces positioned within an upward extension of the plane of outer side face of the side plate 26 or inwardly of the extension. The evaporator 1 can be housed in a case C without leaving any useless space therein, and the case C can therefore be made smaller in size.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*